

	Tower	Floor 樓層	Flats 單位					Floor		Flats 單位					Floor	Flats 單位						
	座數		A	В	С	D	E	F	樓層	A	В	С	D	E	F	樓層	A	В	С	D	E	F
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	第3座 (3A)	7/F-12/F 7樓至12樓	135, 150	135, 150	150	135, 150	135, 150	135, 150	15/F	150	150	150	150	150	150	25要全26要	135, 150	135, 150	150	135, 150	135, 150	135, 150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面具上一層石屎地台面之高度距離)(毫米)			3120	3120	3120	3120	3120	3120		3120, 3170, 3370, 3420	3120, 3170, 3370, 3420	3120, 3370, 3420	3120, 3170, 3370, 3420	3120, 3170, 3370, 3420	3120, 3370, 3420		3120	3120	3120	3120	3120	3120
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	第3座 (3B)	7/F-12/F 7樓至12樓	135, 150	150	135, 150	135, 150, 200	150	150	15/F	150	150	150	150, 200	150	150	17/F-23/F, 25/F-26/F 17樓至23樓, 25樓至26樓	135, 150	150	135, 150	135, 150, 200	150	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層奧層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高貨距離)(毫米)			3120	3120	3120	3120	3120	3120		3120, 3170, 3370, 3420	3120, 3370, 3420	3120, 3370, 3420	3120, 3170, 3370, 3420	3120, 3370, 3420	3120, 3370, 3420		3120	3120	3120	3120	3120	3120

The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.

- The dimensions in the floor plans are all structural dimensions in millimetre
- 2. (I) The restriction on the minimum number of residential units (as referred to in Special Condition No. (16)(b) (i)(x)(I) of the Land Grant) in Phase IX (including Phase IXA, IXB and IXC): 1250

 - (1) The restriction on the minimum number of residential units (as referred to in Special Condition No. (16)(b) (i)(x)(0) of the Land Grant) in Phase K (including Phase IXA, IXB and IXC): 1250
 (II) Special Condition No. (16) (k) of the Land Grant stipulates that except with the prior written consent of the Director of Lands ("the Director"), the Grantee shall not carry out or permit or suffer to be carried out any works in connection with any residential flat erected or to be erected on Site C1, Site C2, Site G, Site H, Site I, Site N and Site O, including but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which shall result in such flat being internally linked to and accessible from any adjoining or adjacent residential flat erected or to be erected on Site C1, Site C2, Site G, Site H, Site I, S
 - (IV) The total number of residential units provided in the Phase: 647

(Remark: Phase IXA forms part of Phase IX)

- 13/F, 14/F, 24/F, 34/F, 44/F, 54/F & 64/F are omitted
- 16/F and 43/F are refuge floors.

因住宅物業的較高樓層的結構牆的厚度遞減、較高樓層的內部面積、一般比較低樓層的內部面積稍大。 備註:

- 樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。
- 批地文件第(16)(b)(i)(x)(l)條特別條款中對於第IX期(包括第IXA期、第IXB期及第IXC期)中住宅單位的最少數目的限制: 1250 (I)

 - (IV) 期數所提供的住宅單位總數:647

(備註:第IXA期屬第IX期一部分)

- 不設 13 樓、14 樓、24 樓、34 樓、44 樓、54 樓及 64 樓。

